



RRC-SERIES

The Rotar Rail Cutter incorporates fast cycle times and incredible cutting power to process tons of rail in the blink of an eye.

The RRC Series has a superior rotating upper head design. This includes heavy-duty, double-rowed slewing ring and bearing with torque hydraulic motor and gearbox. The mounting head allows for carrier interchangeability when needed.

Upper Head & Slewing Ring

The hydraulic cylinder with a pressure relief valve, developed by Rotar, guarantees maximum cutting force under controlled circumstances.

Special Developed Hydraulic Cylinder

The double hose connection on the swivel and large diameter of hoses, bores, and pipes creates optimum oil flow. This connection stops heat building up in the hydraulic system, reducing the RRC's fuel consumption.

Double Hose Connection



RIDE
WITH
US



Specifications

The RRC has a rotating upper head and heavy-duty slewing ring for better positioning on material to be cut. Rotar Designed cutting jaw produces maximum breaking force with minimal hydraulic spiking.



Specification	Unit	RRC-SERIES
		25 R
Machine Class - Boom	ton [^]	25
Machine Class - Dipper	ton [^]	38
Weight	lbs	7,716
Opening Max	in	8
O.A.L.	in	114
Hydraulic Flow Max.	gpm	118
Operating Press Max.	psi	3,625

[^]metric ton